



NLC TAMILNADU POWER LIMITED
 [A JV between NLC India Ltd(formerly Neyveli Lignite Corporation Ltd) &TANGEDCO and subsidiary of NLC India Ltd]
Contracts & Purchase Division
Office of Chief Executive Officer
2x500 MW Thermal Power Plant,
Harbour Estate,Tuticorin-628004. Tamilnadu, India.

Phone: 0461-2352844, 2352840
 Fax: 0461-2352480
 Email:ceo.ntpl@nlcindia.com, candp.ntpl@nlcindia.com

CIN:
U40102TN2005GOI058050
GST NO.:
33AACCN3238N1ZD

निविदा जाँच सं: /TENDER ENQUIRY NO :ENQ/NTPL/18-19/000440/C&P01(01)

दिनांक/DATE
:07/01/2019

पृष्ठ /Page - 1

Due Date of Cover-I Opening : 24/01/2019 11:00:00 hrs. IST (Check NTPL eproc website for any change in due date of opening.)
Note : Quotation should be valid for 60 days from the date of opening.

Gentlemen,
 We shall be glad to receive your lowest online offer submitted through <http://eproc.ntplpower.com> for the material mentioned below, subject to our terms and conditions. Any other mode of offer will be rejected. Please indicate the enquiry number in all future correspondence. Offer details of the participating bidders will be available online after the tender is opened.

क्र.सं. SI No.	विवरण Details	माप की इकाई UOM	मात्रा Quantity																				
1	<p align="center">विनिर्देश Specification</p> <p>21 012 0165 : PTFE TEFLON SHEET 0.5MM THICK. MINIMUM WIDTH 300MM X LENGTH 300MM</p> <table border="1"> <thead> <tr> <th>क्र.सं. SI No.</th> <th>तकनीकी कारक Technical Factor(s)</th> </tr> </thead> <tbody> <tr><td>1</td><td>1.Hardness - 55-58 shore D</td></tr> <tr><td>2</td><td>Tensile strength - 210 Kilogram per Sq.cm,</td></tr> <tr><td>3</td><td>Temperature range: with stand more than 150 Degree Celsius,</td></tr> <tr><td>4</td><td>Colour - WHITE</td></tr> <tr><td>5</td><td>Should have smooth finished surface and does not have bubbles and cracks</td></tr> <tr><td>6</td><td>Should have excellent gasketing property.</td></tr> </tbody> </table> <p align="center">वितरण अनुसूची Delivery Schedule</p> <table border="1"> <thead> <tr> <th>Delivery Type</th> <th>Period From PO Date (Days)</th> <th>Quantity</th> </tr> </thead> <tbody> <tr> <td>Bulk</td> <td>1 to 60</td> <td>10.0000</td> </tr> </tbody> </table> <p align="center">परीक्षण प्रमाणपत्र Test Certificate</p> <p>Test Certificates issued by National Accreditation Board for Testing and Calibration Laboratories (NABL) shall be produced during delivery of materials.</p>	क्र.सं. SI No.	तकनीकी कारक Technical Factor(s)	1	1.Hardness - 55-58 shore D	2	Tensile strength - 210 Kilogram per Sq.cm,	3	Temperature range: with stand more than 150 Degree Celsius,	4	Colour - WHITE	5	Should have smooth finished surface and does not have bubbles and cracks	6	Should have excellent gasketing property.	Delivery Type	Period From PO Date (Days)	Quantity	Bulk	1 to 60	10.0000	Number	10.0000
क्र.सं. SI No.	तकनीकी कारक Technical Factor(s)																						
1	1.Hardness - 55-58 shore D																						
2	Tensile strength - 210 Kilogram per Sq.cm,																						
3	Temperature range: with stand more than 150 Degree Celsius,																						
4	Colour - WHITE																						
5	Should have smooth finished surface and does not have bubbles and cracks																						
6	Should have excellent gasketing property.																						
Delivery Type	Period From PO Date (Days)	Quantity																					
Bulk	1 to 60	10.0000																					
2	<p align="center">विनिर्देश Specification</p> <p>21 012 0166 : PTFE TEFLON SHEET 2.0MM THICK MINIMUM WIDTH 300MM X LENGTH 300MM</p> <table border="1"> <thead> <tr> <th>क्र.सं. SI No.</th> <th>तकनीकी कारक Technical Factor(s)</th> </tr> </thead> <tbody> <tr><td>1</td><td>Hardness - 55-58 shore D</td></tr> <tr><td>2</td><td>Tensile strength - 210 Kilogram per Sq.cm</td></tr> </tbody> </table>	क्र.सं. SI No.	तकनीकी कारक Technical Factor(s)	1	Hardness - 55-58 shore D	2	Tensile strength - 210 Kilogram per Sq.cm	Number	20.0000														
क्र.सं. SI No.	तकनीकी कारक Technical Factor(s)																						
1	Hardness - 55-58 shore D																						
2	Tensile strength - 210 Kilogram per Sq.cm																						

एनटीपीएल स्टोर्स ट्युटोरिन में आपके प्रस्ताव को दरवाजा डिलीवरी आधार पर होना चाहिए।
 YOUR OFFER SHOULD BE ON DOOR DELIVERY BASIS AT NTPL STORES TUTICORIN
 निरीक्षण बंध /Inspection Clause : Inspection at Tuticorin

Basis of Evaluation : Item-wise.

संलग्नक Terms and Conditions of Enquiry
 Attachments :



NLC TAMILNADU POWER LIMITED
 [A JV between NLC India Ltd(formerly Neyveli Lignite Corporation Ltd) & TANGEDCO and subsidiary of NLC India Ltd]
Contracts & Purchase Division
Office of Chief Executive Officer
2x500 MW Thermal Power Plant,
Harbour Estate, Tuticorin-628004, Tamilnadu, India.

Phone: 0461-2352844, 2352840
 Fax: 0461-2352480
 Email: ceo.ntpl@nlcindia.com, candp.ntpl@nlcindia.com

CIN:
U40102TN2005GOI058050
GST NO.:
33AACCN3238N1ZD

निविदा जाँच सं: /TENDER ENQUIRY NO :ENQ/NTPL/18-19/000440/C&P01(01)

दिनांक/DATE
:07/01/2019

पृष्ठ /Page - 2

क्र.सं. SI No.	विवरण Details	माप की इकाई UOM	मात्रा Quantity
-------------------	------------------	--------------------	--------------------

3	Temperature range: with stand more than 150 Degree Celsius
4	Colour - WHITE
5	Should have smooth finished surface and does not have bubbles and cracks
6	Should have excellent gasketing property

वितरण अनुसूची Delivery Schedule		
Delivery Type	Period From PO Date (Days)	Quantity
Bulk	1 to 60	20.0000

परीक्षण प्रमाणपत्र Test Certificate	
Test Certificates issued by National Accreditation Board for Testing and Calibration Laboratories (NABL) shall be produced during delivery of materials.	

क्र.सं. SI No.	विवरण Details	माप की इकाई UOM	मात्रा Quantity
-------------------	------------------	--------------------	--------------------

विनिर्देश Specification	
21 012 0167 : PTFE TEFLON SHEET 3.0MM THICK MINIMUM WIDTH 300MM X LENGTH 300MM	
क्र.सं. SI No.	तकनीकी कारक Technical Factor(s)
1	Hardness - 55-58 shore D,
2	Tensile strength - 210 Kilogram per Sq.cm
3	Temperature range: with stand more than 150 Degree Celsius
4	Colour - WHITE
5	Should have smooth finished surface and does not have bubbles and cracks,
6	Should have excellent gasketing property.

वितरण अनुसूची Delivery Schedule		
Delivery Type	Period From PO Date (Days)	Quantity
Bulk	1 to 60	20.0000

परीक्षण प्रमाणपत्र Test Certificate	
Test Certificates issued by National Accreditation Board for Testing and Calibration Laboratories (NABL) shall be produced during delivery of materials.	

क्र.सं. SI No.	विवरण Details	माप की इकाई UOM	मात्रा Quantity
-------------------	------------------	--------------------	--------------------

विनिर्देश Specification	
21 012 0170 : PTFE TEFLON SHEET 1.0MM THICK MINIMUM WIDTH 300MM X LENGTH 300MM	
क्र.सं. SI No.	तकनीकी कारक Technical Factor(s)
1	Hardness - 55-58 shore D,
2	Tensile strength - 210 Kilogram per Sq.cm

मुख्य कार्यकारी अधिकारी के लिए - एनटीपीएल

For Chief Executive Officer- NTPL



NLC TAMILNADU POWER LIMITED
 [A JV between NLC India Ltd(formerly Neyveli Lignite Corporation Ltd) & TANGEDCO and subsidiary of NLC India Ltd]
Contracts & Purchase Division
Office of Chief Executive Officer
2x500 MW Thermal Power Plant,
Harbour Estate, Tuticorin-628004, Tamilnadu, India.

Phone: 0461-2352844, 2352840
 Fax: 0461-2352480
 Email: ceo.ntpl@nclindia.com, candp.ntpl@nclindia.com

CIN:
U40102TN2005GOI058050
GST NO.:
33AACCN3238N1ZD

निविदा जाँच सं: /TENDER ENQUIRY NO :ENQ/NTPL/18-19/000440/C&P01(01)

दिनांक/DATE
:07/01/2019

पृष्ठ /Page - 3

क्र.सं. SI No.	विवरण Details	माप की इकाई UOM	मात्रा Quantity																				
	<table border="1"> <tr><td>3</td><td>Temperature range: with stand more than 150 Degree Celsius,</td></tr> <tr><td>4</td><td>Colour - WHITE</td></tr> <tr><td>5</td><td>Should have smooth finished surface and does not have bubbles and cracks,</td></tr> <tr><td>6</td><td>Should have excellent gasketing property.</td></tr> </table> <p align="center">वितरण अनुसूची Delivery Schedule</p> <table border="1"> <thead> <tr> <th>Delivery Type</th> <th>Period From PO Date (Days)</th> <th>Quantity</th> </tr> </thead> <tbody> <tr> <td>Bulk</td> <td>1 to 60</td> <td>20.0000</td> </tr> </tbody> </table> <p align="center">परीक्षण प्रमाणपत्र Test Certificate</p> <p>Test Certificates issued by National Accreditation Board for Testing and Calibration Laboratories (NABL) shall be produced during delivery of materials.</p>	3	Temperature range: with stand more than 150 Degree Celsius,	4	Colour - WHITE	5	Should have smooth finished surface and does not have bubbles and cracks,	6	Should have excellent gasketing property.	Delivery Type	Period From PO Date (Days)	Quantity	Bulk	1 to 60	20.0000								
3	Temperature range: with stand more than 150 Degree Celsius,																						
4	Colour - WHITE																						
5	Should have smooth finished surface and does not have bubbles and cracks,																						
6	Should have excellent gasketing property.																						
Delivery Type	Period From PO Date (Days)	Quantity																					
Bulk	1 to 60	20.0000																					
5	<p align="center">विनिर्देश Specification</p> <p>21 012 0331 : PTFE TEFLON SHEET 4.0MM THICK MINIMUM WIDTH 300MM X LENGTH 300MM</p> <table border="1"> <thead> <tr> <th>क्र.सं. SI No.</th> <th>तकनीकी कारक Technical Factor(s)</th> </tr> </thead> <tbody> <tr><td>1</td><td>Hardness - 55-58 shore D</td></tr> <tr><td>2</td><td>Tensile strength - 210 Kilogram per Sq.cm</td></tr> <tr><td>3</td><td>Temperature range: with stand more than 150 Degree Celsius</td></tr> <tr><td>4</td><td>Colour - WHITE</td></tr> <tr><td>5</td><td>Should have smooth finished surface and does not have bubbles and cracks</td></tr> <tr><td>6</td><td>Should have excellent gasketing property</td></tr> </tbody> </table> <p align="center">वितरण अनुसूची Delivery Schedule</p> <table border="1"> <thead> <tr> <th>Delivery Type</th> <th>Period From PO Date (Days)</th> <th>Quantity</th> </tr> </thead> <tbody> <tr> <td>Bulk</td> <td>1 to 60</td> <td>20.0000</td> </tr> </tbody> </table> <p align="center">परीक्षण प्रमाणपत्र Test Certificate</p> <p>Test Certificates issued by National Accreditation Board for Testing and Calibration Laboratories (NABL) shall be produced during delivery of materials.</p>	क्र.सं. SI No.	तकनीकी कारक Technical Factor(s)	1	Hardness - 55-58 shore D	2	Tensile strength - 210 Kilogram per Sq.cm	3	Temperature range: with stand more than 150 Degree Celsius	4	Colour - WHITE	5	Should have smooth finished surface and does not have bubbles and cracks	6	Should have excellent gasketing property	Delivery Type	Period From PO Date (Days)	Quantity	Bulk	1 to 60	20.0000	Number	20.0000
क्र.सं. SI No.	तकनीकी कारक Technical Factor(s)																						
1	Hardness - 55-58 shore D																						
2	Tensile strength - 210 Kilogram per Sq.cm																						
3	Temperature range: with stand more than 150 Degree Celsius																						
4	Colour - WHITE																						
5	Should have smooth finished surface and does not have bubbles and cracks																						
6	Should have excellent gasketing property																						
Delivery Type	Period From PO Date (Days)	Quantity																					
Bulk	1 to 60	20.0000																					