



NLC TAMILNADU POWER LIMITED
 [A JV between NLC India Ltd(formerly Neyveli Lignite Corporation Ltd) &TANGEDCO and subsidiary of NLC India Ltd]
Contracts & Purchase Division
Office of Chief Executive Officer
2x500 MW Thermal Power Plant,
Harbour Estate,Tuticorin-628004. Tamilnadu, India.

Phone: 0461-2352844, 2352840
 Fax: 0461-2352480
 Email:ceo.ntpl@nlcindia.com, candp.ntpl@nlcindia.com

CIN:
U40102TN2005GOI058050
GST NO.:
33AACCN3238N1ZD

निविदा जाँच सं: /TENDER ENQUIRY NO :ENQ/NTPL/19-20/000005/C&P01(01) दिनांक/DATE :07/05/2019 पृष्ठ /Page - 1

Due Date of Cover-I Opening : 28/05/2019 15:00:00 hrs. IST (Check NTPL eproc website for any change in due date of opening.)
Note : Quotation should be valid for 60 days from the date of opening.

Gentlemen,
 We shall be glad to receive your lowest online offer submitted through <http://eproc.ntplpower.com> for the material mentioned below, subject to our terms and conditions. Any other mode of offer will be rejected. Please indicate the enquiry number in all future correspondence. Offer details of the participating bidders will be available online after the tender is opened.

क्र.सं. SI No.	विवरण Details	माप की इकाई UOM	मात्रा Quantity										
1	<p align="center">विनिर्देश Specification</p> <p>29 004 0021 : Fire Bucket strictly confirming to IS ; 2546/1974 and ISI marked, IS:2546/1974 manufactured of 1mm thickness M.S.sheet and diameter of beading wire shall be 3.55 mm. The body shall be two halves which shall be joined together by butt welding. All other requirements shall be as per IS:2546/1974.</p> <table border="1"> <thead> <tr> <th>क्र.सं. SI No.</th> <th>तकनीकी कारक Technical Factor(s)</th> </tr> </thead> <tbody> <tr> <td align="center">1</td> <td>Fire Bucket strictly confirming to IS ; 2546/1974 and ISI marked, IS:2546/1974 manufactured of 1mm thickness M.S.sheet and diameter of beading wire shall be 3.55 mm. The body shall be two halves which shall be joined together by butt welding. All other requirements shall be as per IS:2546/1974.</td> </tr> </tbody> </table> <p align="center">वितरण अनुसूची Delivery Schedule</p> <table border="1"> <thead> <tr> <th>Delivery Type</th> <th>Period From PO Date (Days)</th> <th>Quantity</th> </tr> </thead> <tbody> <tr> <td>Bulk in quantity</td> <td align="center">0 to 90</td> <td align="center">10.0000</td> </tr> </tbody> </table>	क्र.सं. SI No.	तकनीकी कारक Technical Factor(s)	1	Fire Bucket strictly confirming to IS ; 2546/1974 and ISI marked, IS:2546/1974 manufactured of 1mm thickness M.S.sheet and diameter of beading wire shall be 3.55 mm. The body shall be two halves which shall be joined together by butt welding. All other requirements shall be as per IS:2546/1974.	Delivery Type	Period From PO Date (Days)	Quantity	Bulk in quantity	0 to 90	10.0000	Number	10.0000
क्र.सं. SI No.	तकनीकी कारक Technical Factor(s)												
1	Fire Bucket strictly confirming to IS ; 2546/1974 and ISI marked, IS:2546/1974 manufactured of 1mm thickness M.S.sheet and diameter of beading wire shall be 3.55 mm. The body shall be two halves which shall be joined together by butt welding. All other requirements shall be as per IS:2546/1974.												
Delivery Type	Period From PO Date (Days)	Quantity											
Bulk in quantity	0 to 90	10.0000											
2	<p align="center">विनिर्देश Specification</p> <p>29 010 0222 : Bolt cutters are designed for cutting rod, wire mesh, concrete form ties cable and bolts. Slim heads permit cutting close to surface. The high carbon machined steel jaws on the bolt cutters are fully adajustable to maintain a perfect cutting edge. Angled grips for comfortable ,easy handling. The jaws are made of hardened alloy steel. Jaws are adjustable and replaceable. Tubular steel handles with angled grips allow maximum leverage. Lengths shall be 24" and weight shall be 5.3 lbs.(approximately).</p> <table border="1"> <thead> <tr> <th>क्र.सं. SI No.</th> <th>तकनीकी कारक Technical Factor(s)</th> </tr> </thead> <tbody> <tr> <td align="center">1</td> <td>1.The high carbon machined steel jaws on the bolt cutters are fully adajustable to maintain a perfect cutting edge. Angled grips for comfortable ,easy handling. 2.The jaws are made of hardened alloy steel. 3.Jaws are adjustable and replaceable. 4.Tubular steel handles with angled grips allow maximum leverage. 5.Lengths shall be 24" and weight shall be 5.3 lbs.(approximately).</td> </tr> </tbody> </table>	क्र.सं. SI No.	तकनीकी कारक Technical Factor(s)	1	1.The high carbon machined steel jaws on the bolt cutters are fully adajustable to maintain a perfect cutting edge. Angled grips for comfortable ,easy handling. 2.The jaws are made of hardened alloy steel. 3.Jaws are adjustable and replaceable. 4.Tubular steel handles with angled grips allow maximum leverage. 5.Lengths shall be 24" and weight shall be 5.3 lbs.(approximately).	Number	2.0000						
क्र.सं. SI No.	तकनीकी कारक Technical Factor(s)												
1	1.The high carbon machined steel jaws on the bolt cutters are fully adajustable to maintain a perfect cutting edge. Angled grips for comfortable ,easy handling. 2.The jaws are made of hardened alloy steel. 3.Jaws are adjustable and replaceable. 4.Tubular steel handles with angled grips allow maximum leverage. 5.Lengths shall be 24" and weight shall be 5.3 lbs.(approximately).												

एनटीपीएल स्टोर्स टुटिकोरिन में आपके प्रस्ताव को दरवाजा डिलीवरी आधार पर होना चाहिए।
 YOUR OFFER SHOULD BE ON DOOR DELIVERY BASIS AT NTPL STORES TUTICORIN
 निरीक्षण बंध /Inspection Clause : Inspection at Tuticorin
 गारंटी की आवश्यकताएँ /Guarantee Requirement : General Guarantee for Warranty as per NTPL format Warranty Period: 12 months from the date of commissioning or 18 months from the date of receipt of material, whichever is earlier.

Basis of Evaluation : Item-wise.

संलग्नक Terms and Conditions of Enquiry
 Attachments :



NLC TAMILNADU POWER LIMITED
 [A JV between NLC India Ltd(formerly Neyveli Lignite Corporation Ltd) &TANGEDCO and subsidiary of NLC India Ltd]
Contracts & Purchase Division
Office of Chief Executive Officer
2x500 MW Thermal Power Plant,
Harbour Estate,Tuticorin-628004. Tamilnadu, India.

Phone: 0461-2352844, 2352840
 Fax: 0461-2352480
 Email:ceo.ntpl@nlcindia.com, candp.ntpl@nlcindia.com

CIN:
U40102TN2005GOI058050
GST NO.:
33AACCN3238N1ZD

निविदा जाँच सं: /TENDER ENQUIRY NO :ENQ/NTPL/19-20/000005/C&P01(01)

दिनांक/DATE
:07/05/2019

पृष्ठ /Page - 2

क्र.सं. SI No.	विवरण Details	माप की इकाई UOM	मात्रा Quantity										
	<p align="center">वितरण अनुसूची Delivery Schedule</p> <table border="1"> <thead> <tr> <th>Delivery Type</th> <th>Period From PO Date (Days)</th> <th>Quantity</th> </tr> </thead> <tbody> <tr> <td>bulk in quantity</td> <td>0 to 90</td> <td>2.0000</td> </tr> </tbody> </table> <p align="center">परीक्षण प्रमाणपत्र Test Certificate</p> <p>Manufacturers test certificate is required</p>	Delivery Type	Period From PO Date (Days)	Quantity	bulk in quantity	0 to 90	2.0000						
Delivery Type	Period From PO Date (Days)	Quantity											
bulk in quantity	0 to 90	2.0000											
3	<p align="center">विनिर्देश Specification</p> <p>29 010 0223 : 1.Petrol driven circular saw should have displacement of more or less 64cc, wheel dia between 300-325mm. 2.Fuel tank not more than one (01) litre , cutting capacity between 125-130mm and weight not exceed 11kgs. 3.Power output of 2.3Hp/1.7Kw</p> <table border="1"> <thead> <tr> <th>क्र.सं. SI No.</th> <th>तकनीकी कारक Technical Factor(s)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>1.Petrol driven circular saw should have displacement of more or less 64cc, wheel dia between 300-325mm. 2.Fuel tank not more than one (01) litre , cutting capacity between 125-130mm and weight not exceed 11kgs. 3.Power output of 2.3Hp/1.7Kw 4.Maximum power speed of 11000 rpm. 5.Idling speed of 3000 rpm 6. Recommended bar length of 14" to 16" 6.Recommended bar length of 14" to 16"</td> </tr> </tbody> </table> <p align="center">वितरण अनुसूची Delivery Schedule</p> <table border="1"> <thead> <tr> <th>Delivery Type</th> <th>Period From PO Date (Days)</th> <th>Quantity</th> </tr> </thead> <tbody> <tr> <td>Bulk in Quantity</td> <td>0 to 90</td> <td>2.0000</td> </tr> </tbody> </table> <p align="center">परीक्षण प्रमाणपत्र Test Certificate</p> <p>Manufacturers test certificate is required</p>	क्र.सं. SI No.	तकनीकी कारक Technical Factor(s)	1	1.Petrol driven circular saw should have displacement of more or less 64cc, wheel dia between 300-325mm. 2.Fuel tank not more than one (01) litre , cutting capacity between 125-130mm and weight not exceed 11kgs. 3.Power output of 2.3Hp/1.7Kw 4.Maximum power speed of 11000 rpm. 5.Idling speed of 3000 rpm 6. Recommended bar length of 14" to 16" 6.Recommended bar length of 14" to 16"	Delivery Type	Period From PO Date (Days)	Quantity	Bulk in Quantity	0 to 90	2.0000	Number	2.0000
क्र.सं. SI No.	तकनीकी कारक Technical Factor(s)												
1	1.Petrol driven circular saw should have displacement of more or less 64cc, wheel dia between 300-325mm. 2.Fuel tank not more than one (01) litre , cutting capacity between 125-130mm and weight not exceed 11kgs. 3.Power output of 2.3Hp/1.7Kw 4.Maximum power speed of 11000 rpm. 5.Idling speed of 3000 rpm 6. Recommended bar length of 14" to 16" 6.Recommended bar length of 14" to 16"												
Delivery Type	Period From PO Date (Days)	Quantity											
Bulk in Quantity	0 to 90	2.0000											
4	<p align="center">विनिर्देश Specification</p> <p>29 018 0008 : HAND HACK SAW : Size: minimum 12 inch with handle : wood.</p> <table border="1"> <thead> <tr> <th>क्र.सं. SI No.</th> <th>तकनीकी कारक Technical Factor(s)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Size: 24" with handle : wood</td> </tr> </tbody> </table> <p align="center">वितरण अनुसूची Delivery Schedule</p> <table border="1"> <thead> <tr> <th>Delivery Type</th> <th>Period From PO Date (Days)</th> <th>Quantity</th> </tr> </thead> <tbody> <tr> <td>bulk in quantity</td> <td>0 to 90</td> <td>2.0000</td> </tr> </tbody> </table>	क्र.सं. SI No.	तकनीकी कारक Technical Factor(s)	1	Size: 24" with handle : wood	Delivery Type	Period From PO Date (Days)	Quantity	bulk in quantity	0 to 90	2.0000	Number	2.0000
क्र.सं. SI No.	तकनीकी कारक Technical Factor(s)												
1	Size: 24" with handle : wood												
Delivery Type	Period From PO Date (Days)	Quantity											
bulk in quantity	0 to 90	2.0000											
5	<p align="center">विनिर्देश Specification</p>	Number	20.0000										

मुख्य कार्यकारी अधिकारी के लिए - एनटीपीएल

For Chief Executive Officer- NTPL



NLC TAMILNADU POWER LIMITED
 [A JV between NLC India Ltd(formerly Neyveli Lignite Corporation Ltd) &TANGEDCO and subsidiary of NLC India Ltd]
Contracts & Purchase Division
Office of Chief Executive Officer
2x500 MW Thermal Power Plant,
Harbour Estate,Tuticorin-628004. Tamilnadu, India.

Phone: 0461-2352844, 2352840
 Fax: 0461-2352480
 Email:ceo.ntpl@nlcindia.com, candp.ntpl@nlcindia.com

CIN:
U40102TN2005GOI058050
GST NO.:
33AACCN3238N1ZD

निविदा जाँच सं: /TENDER ENQUIRY NO :ENQ/NTPL/19-20/000005/C&P01(01)

दिनांक/DATE
:07/05/2019

पृष्ठ /Page - 3

क्र.सं. SI No.	विवरण Details	माप की इकाई UOM	मात्रा Quantity										
	<p>29 999 1360 : The fire man axe should be made of carbon steel (Type - B Axe with insulated steel handle). The insulation should be of special semi hard vulcanized rubber or equivalent material capable of withstanding 20,000 V. The fireman Axe should be strictly as per IS:926-1985.</p> <table border="1"> <thead> <tr> <th>क्र.सं. SI No.</th> <th>तकनीकी कारक Technical Factor(s)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>1.The fire man axe should be made of carbon steel (Type-B Axe with insulated steel handle). 2.The insulation should be of special semi hard vulcanized rubber or equivalent material capable of withstanding 20,000 V. The fireman Axe should be strictly as per IS:926-1985.</td> </tr> </tbody> </table> <p align="center">वितरण अनुसूची Delivery Schedule</p> <table border="1"> <thead> <tr> <th>Delivery Type</th> <th>Period From PO Date (Days)</th> <th>Quantity</th> </tr> </thead> <tbody> <tr> <td>BULK in Quantity</td> <td>0 to 90</td> <td>20.0000</td> </tr> </tbody> </table> <p align="center">परीक्षण प्रमाणपत्र Test Certificate</p> <p>Manufacturers test certificate is required</p>	क्र.सं. SI No.	तकनीकी कारक Technical Factor(s)	1	1.The fire man axe should be made of carbon steel (Type-B Axe with insulated steel handle). 2.The insulation should be of special semi hard vulcanized rubber or equivalent material capable of withstanding 20,000 V. The fireman Axe should be strictly as per IS:926-1985.	Delivery Type	Period From PO Date (Days)	Quantity	BULK in Quantity	0 to 90	20.0000		
क्र.सं. SI No.	तकनीकी कारक Technical Factor(s)												
1	1.The fire man axe should be made of carbon steel (Type-B Axe with insulated steel handle). 2.The insulation should be of special semi hard vulcanized rubber or equivalent material capable of withstanding 20,000 V. The fireman Axe should be strictly as per IS:926-1985.												
Delivery Type	Period From PO Date (Days)	Quantity											
BULK in Quantity	0 to 90	20.0000											
6	<p align="center">विनिर्देश Specification</p> <p>29 999 1361 : The pick axe should have solid bamboo handle.</p> <table border="1"> <thead> <tr> <th>क्र.सं. SI No.</th> <th>तकनीकी कारक Technical Factor(s)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>The pick axe should have solid bamboo handle.</td> </tr> </tbody> </table> <p align="center">वितरण अनुसूची Delivery Schedule</p> <table border="1"> <thead> <tr> <th>Delivery Type</th> <th>Period From PO Date (Days)</th> <th>Quantity</th> </tr> </thead> <tbody> <tr> <td>Bulk in quantity</td> <td>0 to 90</td> <td>4.0000</td> </tr> </tbody> </table>	क्र.सं. SI No.	तकनीकी कारक Technical Factor(s)	1	The pick axe should have solid bamboo handle.	Delivery Type	Period From PO Date (Days)	Quantity	Bulk in quantity	0 to 90	4.0000	Number	4.0000
क्र.सं. SI No.	तकनीकी कारक Technical Factor(s)												
1	The pick axe should have solid bamboo handle.												
Delivery Type	Period From PO Date (Days)	Quantity											
Bulk in quantity	0 to 90	4.0000											